

WIRELESS WI-FI / WLAN NETWORK IP SURVEILLANCE CAMERA



WIRELESS WI-FI / WLAN NETWORK IP SURVEILLANCE CAMERA	
Name:	XENET Wireless Wi-Fi/WLAN Network IP Surveillance Camera with Angle Control, Motion Detection, Night Vision, Free DDNS and Microphone
Rotation Angle:	Pan: 355°/ Tilt: 90°
System Security:	Supports three-level account, password, user authority management
DDNS:	Free DDNS bounded
Cell Phone View:	Support I-Phone, Windows Mobile, Android cell phone.
Microcomputer Processor:	32Bit RSIC embedded processor
Wireless:	WIFI, 802.11 b/g/n
Protocol:	Support TCP/IP, HTTP, ICMP, DHCP, FTP, SMTP, PPPoE etc
Network Interface:	RJ-45, 10/100Mb Self-Adaptable Ethernet Slot
Online Visitor:	Support 4 Visitors at the same time
IP Mode:	Dynamic IP address Static IP address PPPOE

Preset:	Support 16 Preset Position
Rotation Speed:	11 level PT speed optional, speed range 15-70°/ second
Night Vision:	10 Φ5 LED
IR Distance:	10m
Signal System:	CMOS 300,000 pixel
Resolution:	VGA(640*480), QVGA(320*240)
Frame Rate:	25fps
Compression Format:	M-JPEG
Lens Standard:	3.6mm
Video Adjustment:	Brightness and Contrast Adjustable Auto White Balance Auto Backlight Compensation
Alarm Detection:	Motion Detection, Motion Detect Sensibility can be adjusted
Alarm Action:	Support Email Photo, FTP Photo etc.
Audio Input / Output:	Built-in Microphone / Built-in Speaker
Audio Interface:	Audio In / Audio Out
Audio Gain:	AGC
Audio Compression:	ADPCM
System Requirement:	Microsoft Win98 SE/ME/2000/XP, Vista, Win 7; browser: IE6.0, IE7.0, IE8.0, Firefox, Google Browser or other standard browser
Shape/ Use Environment:	Cartoon Robot / Indoor Use
Working Temperature:	-10 ~ 50 °C
Working Humidity:	95% RH
Item Size:	10 x 10 x 12.5 cm (L x W x H)
Packaging Size:	20 x 12 x 17.9 cm (L x W x H)
Power:	DC5V 2A